

Antenna cable - RAD-CAB-EF393- 3M - 2867649

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Antenna cable, outside diameter: 10 mm (0.4 in.), inner conductor: stranded, attenuation: 1.0 / 1.8 / 3.1 dB at 0.9 / 2.4 / 5.8 GHz, connection: 2 x N (male), cable length: 3 m (10 ft.)




The figure shows a version of the product

Why buy this product

- Easy installation, thanks to flexible inner conductor
- UV resistant
- Oil-resistant
- Halogen-free
- Flame-retardant



Key Commercial Data

| | |
|--------------|---|
| Packing unit | 1 STK |
| GTIN |  4 017918 939014 |
| GTIN | 4017918939014 |

Technical data

Dimensions

| | |
|--------------------|----------|
| Fixed cable length | 3 m |
| External diameter | 10.00 mm |

Ambient conditions

| | |
|---|-------------------|
| Ambient temperature (operation) | -40 °C ... 105 °C |
| Ambient temperature (storage/transport) | -40 °C ... 105 °C |

General

| | |
|-------------------|----------------------|
| Connection 1 | Connector connection |
| Connection method | N (male) |
| Note | Both sides |

Antenna cable - RAD-CAB-EF393- 3M - 2867649

Technical data

General

| | |
|------------------------|-------------------|
| Connection method | N (male) |
| Cable type | EF 393 |
| Outer sheath, material | RADOX®(LSFH) |
| External sheath, color | black |
| Minimum bending radius | 50.00 mm |
| Frequency range | 0.3 GHz ... 6 GHz |
| Impedance | 50 Ω |

Attenuation

| | |
|---------------|----------------|
| 868 / 900 MHz | approx. 1 dB |
| 2.4 GHz | approx. 1.8 dB |
| 5 GHz | approx. 3.1 dB |

Environmental Product Compliance

| | |
|------------|---|
| REACH SVHC | Lead 7439-92-1 |
| China RoHS | Environmentally Friendly Use Period = 25; |
| | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

| | | |
|-----|---|---------------|
| EAC |  | EAC-Zulassung |
|-----|---|---------------|

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>