

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
H	-	F		EH-1253-96	05-11-97	LvdH	J.G
		G		ECR-07-020965	22-08-08	AEG	MKO
		G1		ECR-11-008320	18NOV11	RK	MKO

NOTES:

- 1 CONNECTOR MEETS THE REQUIREMENTS ACC. DIN 41612,PART 5.
- 2 MATERIAL CONTACT: PHOSPHORBRONZE. MATERIAL HOUSING: GLASSFILLED THERM. POLYESTER. COLOR:GREY
- 3 AT CONTACTAREA 1,25 μm GOLD OVER 1,25 μm NICKEL AT SOLDER POST AREA 1,25 μm TIN.
- 4 AT CONTACTAREA 0,8 μm GOLD OVER 1,25 μm NICKEL AT SOLDER POST AREA 1,25 μm TIN.
- 5 CONTACT ARRANGEMENTS; AN AN ASTERISK " X " DENOTES A SIGNAL CONTACT. AN ASTERISK " ⊗ " DENOTES A KINKED SIGNAL CONTACT.
- 6 AT CONTACTAREA 0,4 μm GOLD OVER 1,25 μm NICKEL AT SOLDER POST AREA 1,25 μm TIN.
- 7 CONNECTOR PRINTED WITH PARTNUMBER AND DATECODE ON OUTSIDE OF MATING AREA AT SIDE OF ROW c.
- 8 SOLDER POSTS SUITABLE FOR 1,0 NOM. P.C.B. HOLES.
- 9 FLUX RESISTANCE STRIP.
- 10 KINKED POSTS.
- 11 AT CONTACTAREA 0,1 μm GOLD OVER 0,7 μm PALLADIUM (DURAGOLD) OVER 1,25 μm NICKEL, AT SOLDERPOST AREA 1,25 μm TIN.

c	b	a	5
⊗	o	⊗	1
X	o	X	2
X	o	X	3
X	o	X	4
X	o	X	5
X	o	X	6
X	o	X	7
X	o	X	8
X	o	X	9
X	o	X	10
X	o	X	11
X	o	X	12
X	o	X	13
X	o	X	14
X	o	X	15
X	o	X	16
X	o	X	17
X	o	X	18
X	o	X	19
X	o	X	20
X	o	X	21
X	o	X	22
X	o	X	23
X	o	X	24
X	o	X	25
X	o	X	26
X	o	X	27
X	o	X	28
X	o	X	29
X	o	X	30
X	o	X	31
⊗	o	⊗	32

OBSOLETE	WITH	WITHOUT	1	2	7-216097-4
OBSOLETE	WITH	WITH	1	2	6-216097-4
OBSOLETE	WITH	WITHOUT	4	2	1-216097-4
OBSOLETE	WITH	WITH	6	2	216097-8
SUPERSEDED BY 2173046-4	WITH	WITH	4	2	216097-4
OBSOLETE	WITH	WITH	3	2	216097-1
	10	9	FINISH	MATERIAL	PARTNUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	J.V.LIEMPT	19JUN91
DIMENSIONS: mm		CHK	J.GIBBELS	19NOV97
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	-	NAME
0 PLC	± 0,1	PRODUCT SPEC	-	
1 PLC	± 0,05	APPLICATION SPEC	-	
2 PLC	± -	WEIGHT	-	
3 PLC	± -	SCALE	A2	00779
4 PLC	± -	SHEET	C=216097	1 of 1
ANGLES	± 0°,30'	REV	G1	
MATERIAL	FINISH	CUSTOMER DRAWING		

TE TE Connectivity

64 POS C FEMALE B.T.B. CONN.
 ACC.DIN 41612 WITH SOLDER POSTS
 FOR 2,4 OR 3,2 mm. P.C.BOARD THK'S.

1471-9 (3/11)

216097

B

A