Rear horizontal rail, centre (E)

When subdividing 6 U into 2 x 3 U, the adaptor rail accommodates the guide rails when fastened to the centre horizontal rail.

- HP pitch pattern of holes for the precise installation of guide rails
- M4 and M2.5 thread on the end face
- Straight-through core hole
- Horizontal rail 192 HP without machining on the end faces. Suitable for cutting to length

Material:
Extruded aluminum section

Surface finish:
Clear-chromated or anodized

Usable width (HP)	Packs of	Order No.
12	1	**3684.587**
16	1	**3684.588**
20	1	**3684.589**
40	1	**3684.964**
42	1	**3684.590**
63	1	**3686.005**
84	1	**3684.591**
84	1	**3685.272**[1)]
858.5 mm	1	**3684.584**
192	1	**3688.004**[2)]

[1)] Including 2 assembly screws
[2)] Anodized

! Also required:

Assembly screws M4 x 12, packs of 100, order no. 3654.300, see page 164





Rear horizontal rail, with channel for Ripac ECO (C7)

To accommodate guide rails and for the attachment of Z rails, insulating strips or conductive strips.

- HP pitch pattern of holes for the precise installation of guide rails
- Channel for slide-in covers
- For mounting backplanes/Z rails, threaded inserts (3684.610) are additionally required
- M4 thread on end face
- Straight-through core hole
- Not suitable for mounting under covers

Material: Extruded aluminum section

Surface finish: Clear-chromated

Usable width (HP)	Packs of	Order No.
84	1	**3688.104**

! Also required:

Assembly screw M4 x 12



Rear horizontal rail, with integral Z rail for Ripac ECO (C8)

To accommodate guide rails. Integral Z rail for mounting connectors to DIN 41612.

- HP pitch pattern of holes for the precise installation of guide rails
- 84 tapped holes M2.5 for connector mounting
- M4 thread on end face
- Straight-through core hole

Material:
Extruded aluminum section

Surface finish:
Clear-chromated

Usable width (HP)	Packs of	Order No.
84	1	**9901.991**

! Also required:

Assembly screws

	Packs of	Order No.
M4 x 12	100	**3654.300**