



规格 Specifications

额定负荷 Ratings	DC 30 V 0.3 A
① 初期接触电阻 Initial Contact Resistance	30 mΩ Max.
绝缘电阻 Insulation Resistance	DC 500 V 60 Sec. 100 MΩ Min.
抗电强度 Dielectric	AC 500 V (50~60HZ) 60 Sec.
操作力 Operating Force (gf)	A = B, B = C, C = D 250 ± 100 200 ± 100 250 ± 100
① 负荷寿命 Operating Life With Load	10,000 次 Cycles

6	弹片	SPRING PLATE	C5210R	1	NATURAL
5	端子	TERMINAL	C2680R	6	Ag PLATED
4	基板	TERMINAL BASE	PHENOL RESIN	1	YELLOW
3	接触片	CONTACT	C5210R	1	Ag CLAD
2	胶柄	KNOB	P O M	1	G 2 - 9
1	铁壳	FRAME	S P C C	1	Sn PLATED
序NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS	

A01	机械寿命 —— 负荷寿命 见① 接触阻抗 —— 初期接触电阻 见①	王光云	06-04-23
02		何景洪	22-12-04
标号 REV	内容 DESCRIPTION	签名 SIGN.	日期 DATE
DWG NO. ITEM1831			

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	SIDE KNOB SLIDE SWITCH	ITEM NO	SK-14D01-G	
UNDER 1	± 0.10	DRAWN	王光云	VERSION	A01	PAGE 1 OF 1
1 - 10	± 0.30	REVIEWED	张念明	SCALE		UNIT mm
OVER 10	± 0.50	APPROVED	林高全	PROJECTION		

**COMAX** ELECTRONICS (HUIZHOU) CO.,LTD.