

規 格 書

Electrical Specification

Model No : PA-1061-0

Part No : PA-1061-02IL-LF

Description : 12V 60W AC Adaptor

Revision : A

Issued Date : Oct. 30, 2012



光寶科技股份有限公司

LITE-ON TECHNOLOGY CORP.

桃園縣大園鄉三石村三和路 3 巷 7 號（力信工業大樓）

7,Lane 3,San Ho Rd,San-Shin Village,Da-Yuan Hsiang,Taoyuan Hsien 337,Taiwan, R.O.C.

Approved By	Checked By	Prepared By
翁文輝	X	林展輝

Change Record			
DCN No	REV	Revision Description	Date
	00	Modified form PA-1061-01LT-LF	Jul. 17, 2012
	X01	1. 2.8 Safety: Hi-pot test from 1800Vac to 1850Vac 2. 4.1 EMS surge from 6KV(DM)/6KV(CM) to 1KV(DM)/2KV(CM) 3. 6.4 Weight from 450g to 320±15g.	Jul. 18, 2012
	X02	1. 6.3 DC cord: From 1500mm change to 1050mm	Oct. 24, 2012
	A	Release to factory	Oct. 30, 2012

Contents

1. Description	4
2. Electrical.....	4
2.1 Input Voltage	4
2.2 Input Frequency	4
2.3 Input Current	4
2.4 Inrush Current	4
2.5 Hold-Up time	4
2.6 Input wattage.....	4
2.7 Efficiency.....	4
2.8 Safety Test	4
2.9 Output Voltage and Current.....	4
2.10 Ripple and Noise.....	5
2.11 Over-Shoot and under-shoot.....	5
2.12 Protection.....	5
2.13 LED Indication.....	5
2.14 Rise time	5
2.15 Turn on delay time.....	5
2.16 Temperature Coeffience	5
2.17 Transient Response	5
3. Environment	6
3.1 Temperature.....	6
3.2 Humidity	6
3.3 Altitude	6
4. EMC	6
4.1 EMS	6
4.2 EMI.....	6
5. Reliability.....	7
5.1 Life (E-cap.).....	7
5.2 M.T.B.F.....	7
5.3 Temperature Rise.....	7
5.4 Burn-in	7
5.5 Vibration Test	7
5.6 Drop-Test.....	7
6. Mechanical	7

1. Description

This product is a AC to DC power transfer device, it can provide for a **60W** single dc output with constant voltage source.

2. Electrical

2.1 Input Voltage

- a. 100 - 240Vac Nominal.
- b. 90 - 264Vac Universal.

2.2 Input Frequency

47- 63Hz.

2.3 Input Current

1.5A max. at 90Vac input & dc output full-loading.

2.4 Inrush Current

Inrush peak current and Joule integral will be measure at different line voltage at high ambient temperature. Peak current is within specified limit and Joule integral well below fuse and bridge spec.

2.5 Hold-Up time

10msec min. at dc output full-loading and 115Vac input.

2.6 Input wattage

Less than **0.3W** at 230Vac input & no load condition.

2.7 Efficiency

Average efficiency **87%** minimum min. at 25%, 50%, 75% & 100% of full-loading and 115/230Vac input (After warm up 20 minutes).

2.8 Safety Test

- a. Leakage current less than **0.25 mA** at 254Vac, 50Hz.
- b. Hi-Pot test : **1850 Vac**, 10mA, 1 – 3 Sec. between Primary to Secondary ground.
- c. Insulation resistance: at dc 500Vdc, 1 Sec. between Primary to Secondary circuit, IR shall $\geq 20M\Omega$.
- d. Grounding test : AC 30A , 2 Sec. between input safety ground and SELV output GND, GR $\leq 0.1 \Omega$.

2.9 Output Voltage and Current

Vout (V)	Range (V)	Iout (min., A)	Iout (max., A)	Peak (10S, A)
12V	11.4 – 12.6	0	5	6

2.10 Ripple and Noise

Low frequency ripple ($< 100\text{KHz}$) $\leq 300\text{mVpp}$, and Total composite Ripple and Noise. Less than **300mVp-p**, tested by dc loading side parallel with a $10\mu\text{F}/\text{EC}$. and $0.1\mu\text{F}/\text{Ceramic}$. Capacitors and Measured Band Width 20MHz.

2.11 Over-Shoot and under-shoot

Less than 10% of nominal Voltage value.

2.12 Protection

- a. SCP : Short circuit protection with auto. recovery function.
- b. OVP : Over voltage protection with shut down & latch off function.
Tripped voltage will be less than **18Vdc**.
- c. OCP : Over current protection with auto. recovery function,
current limit : **9 A** (max.)
- d. OTP: The adapter shall provide over temperature protection and if the temperature rises to set temperature point, the PSU shall be latch-off.

2.13 LED Indication

Green light for Nominal operation. Blank or Flash for SCP mode.

2.14 Rise time

Rise time shall be less than **50msec.**, it should be measured from 10% to 90% of the output voltage.

2.15 Turn on delay time

The output voltage should turn on from AC on to settle within regulation in less than **3.0sec.**

2.16 Temperature Coeffience

Less than 0.2%/C

2.17 Transient Response

Dynamic loading condition.

DC output (V)	I1 (A)	I2 (A)	dVmax.(V)	Time-max.	dI/dT
12.0	0.0	1.7	+/- 1.0	10 msec.	$\geq 50\text{mA/usec.}$
12.0	1.7	3.4	+/- 1.0	10 msec.	$\geq 50\text{mA/usec.}$
12.0	3.4	5.0	+/- 1.0	10 msec.	$\geq 50\text{mA/usec.}$

50% of duty cycle.

3. Environment

3.1 Temperature

- a. Operation : **0 to 40 °C**
- b. Storage : -40 to 70 °C

3.2 Humidity

- a. Operation : 20 to 80%
- b. Storage : 10 to 90%

3.3 Altitude

From sea level to **2000m** (operation).

4. EMC

4.1 EMS

Test Item	Test Specification	IEC Standards
ESD	Contact +/- 8KV	61000-4-2
ESD	Air +/- 15KV	61000-4-2
RS	FR: 26MHz-1.0GHz, Field Strength: 3V/M	61000-4-3
EFT	+/- 1KV (DM) & +/- 2KV (CM)	61000-4-4
SURGE	+/- 1KV (DM) & +/- 2KV (CM)	61000-4-5
CS	3V/M	61000-4-6
DIPS	0% 250Cy, 40% 5 Cy, 70% 5Cy	61000-4-11

4.2 EMI

Standards	Specification
FCC	Part 15,class B
VCCI	Class B
CISPR	Part 22,class B

5. Reliability

5.1 Life (E-cap.)

12,000 hours (8 hours/day x 300 days/year x 5 years)

At DC output full-loading, AC 115/230 Vac input & ambient temperature 25°C.

5.2 M.T.B.F.

50,000 Power On Hours at 25°C.

5.3 Temperature Rise.

Less than **45°C** at nominal AC input / DC output full-loading and environment temperature 25+/-1°C on Top/Bottom of plastic case.

5.4 Burn-in

100% Burn-In with 80~100% full-loading & 35~45°C Environment temperature.

5.5 Vibration Test

- Non operation vibration with shipping container shall be 2G'S peak/7-50Hz, 4G'S /50-500Hz, after test no abnormally to be found.
- Operation vibration shall be 0.5G'S peak/10-60Hz, 3 AXES, after test no abnormally to be noted.

5.6 Drop-Test

Test height is 100cm, after drop test no function abonormally to be noted.

6. Mechanical

6.1 Plastic enclosure : **PC+ABS** material.

6.2 Physical Size : **120 mm(L) * 60 mm (W) * 35 mm (H).**

6.3 DC cord: **1050 mm, 16** wires.

6.4 Weight : **320±15g.**