

# IRF7317PbF



HEXFET® Power MOSFET

- Generation V Technology
- Ultra Low On-Resistance
- Dual N and P Channel MOSFET
- Surface Mount
- Fully Avalanche Rated
- Lead-Free

## Description

Fifth Generation HEXFETs from International Rectifier utilize advanced processing techniques to achieve extremely low on-resistance per silicon area. This benefit, combined with the fast switching speed and ruggedized device design that HEXFET Power MOSFETs are well known for, provides the designer with an extremely efficient and reliable device for use in a wide variety of applications.

The SO-8 has been modified through a customized leadframe for enhanced thermal characteristics and multiple-die capability making it ideal in a variety of power applications. With these improvements, multiple devices can be used in an application with dramatically reduced board space. The package is designed for vapor phase, infra red, or wave soldering techniques.



## Absolute Maximum Ratings ( $T_A = 25^\circ\text{C}$ Unless Otherwise Noted)

	Symbol	Maximum		Units
		N-Channel	P-Channel	
Drain-Source Voltage	$V_{DS}$	20	-20	
Gate-Source Voltage	$V_{GS}$	± 12		
Continuous Drain Current <sup>①</sup>	$T_A = 25^\circ\text{C}$ $T_A = 70^\circ\text{C}$	6.6	-5.3	A
		5.3	-4.3	
Pulsed Drain Current	$I_{DM}$	26	-21	
Continuous Source Current (Diode Conduction)	$I_S$	2.5	-2.5	
Maximum Power Dissipation <sup>②</sup>	$T_A = 25^\circ\text{C}$ $T_A = 70^\circ\text{C}$	2.0		W
		1.3		
Single Pulse Avalanche Energy	$E_{AS}$	100	150	mJ
Avalanche Current	$I_{AR}$	4.1	-2.9	A
Repetitive Avalanche Energy	$E_{AR}$	0.20		mJ
Peak Diode Recovery $dv/dt$ <sup>③</sup>	$dv/dt$	5.0	-5.0	V/ ns
Junction and Storage Temperature Range	$T_J, T_{STG}$	-55 to + 150 °C		

## Thermal Resistance Ratings

Parameter	Symbol	Limit	Units
Maximum Junction-to-Ambient <sup>④</sup>	$R_{\theta JA}$	62.5	°C/W

# IRF7317PbF

International  
**IR** Rectifier

## Electrical Characteristics @ T<sub>J</sub> = 25°C (unless otherwise specified)


Parameter	Min.	Typ.	Max.	Units	Conditions	
						Parameter
V <sub>(BR)DSS</sub>	N-Ch	20	—	—	V	V <sub>GS</sub> = 0V, I <sub>D</sub> = 250μA
	P-Ch	-20	—	—		V <sub>GS</sub> = 0V, I <sub>D</sub> = -250μA
ΔV <sub>(BR)DSS</sub> /ΔT <sub>J</sub>	N-Ch	—	0.027	—	V/°C	Reference to 25°C, I <sub>D</sub> = 1mA
	P-Ch	—	0.031	—		Reference to 25°C, I <sub>D</sub> = -1mA
R <sub>DS(ON)</sub>	N-Ch	—	0.023	0.029	Ω	V <sub>GS</sub> = 4.5V, I <sub>D</sub> = 6.0A ④
		—	0.030	0.046		V <sub>GS</sub> = 2.7V, I <sub>D</sub> = 5.2A ④
	P-Ch	—	0.049	0.058		V <sub>GS</sub> = -4.5V, I <sub>D</sub> = -2.9A ④
		—	0.082	0.098		V <sub>GS</sub> = -2.7V, I <sub>D</sub> = -1.5A ④
V <sub>GS(th)</sub>	N-Ch	0.7	—	—	V	V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 250μA
	P-Ch	-0.7	—	—		V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = -250μA
g <sub>fs</sub>	N-Ch	—	20	—	S	V <sub>DS</sub> = 10V, I <sub>D</sub> = 6.0A ④
	P-Ch	—	5.9	—		V <sub>DS</sub> = -10V, I <sub>D</sub> = -1.5A ④
I <sub>DSS</sub>	N-Ch	—	—	1.0	μA	V <sub>DS</sub> = 16V, V <sub>GS</sub> = 0V
	P-Ch	—	—	-1.0		V <sub>DS</sub> = -16V, V <sub>GS</sub> = 0V
	N-Ch	—	—	5.0		V <sub>DS</sub> = 16V, V <sub>GS</sub> = 0V, T <sub>J</sub> = 55°C
	P-Ch	—	—	-25		V <sub>DS</sub> = -16V, V <sub>GS</sub> = 0V, T <sub>J</sub> = 55°C
I <sub>GSS</sub>	N-P	—	—	±100	nA	V <sub>GS</sub> = ±12V
Q <sub>g</sub>	N-Ch	—	18	27	nC	N-Channel I <sub>D</sub> = 6.0A, V <sub>DS</sub> = 10V, V <sub>GS</sub> = 4.5V ④
	P-Ch	—	19	29		
Q <sub>gs</sub>	N-Ch	—	2.2	3.3	nC	P-Channel I <sub>D</sub> = -2.9A, V <sub>DS</sub> = -16V, V <sub>GS</sub> = -4.5V
	P-Ch	—	4.0	6.1		
Q <sub>gd</sub>	N-Ch	—	6.2	9.3	nC	N-Channel V <sub>DD</sub> = 10V, I <sub>D</sub> = 1.0A, R <sub>G</sub> = 6.0Ω, R <sub>D</sub> = 10Ω ④
	P-Ch	—	7.7	12		
t <sub>d(on)</sub>	N-Ch	—	8.1	12	ns	P-Channel V <sub>DD</sub> = -10V, I <sub>D</sub> = -2.9A, R <sub>G</sub> = 6.0Ω, R <sub>D</sub> = 3.4Ω ④
	P-Ch	—	15	22		
t <sub>r</sub>	N-Ch	—	17	25	ns	N-Channel V <sub>GS</sub> = 0V, V <sub>DS</sub> = 15V, f = 1.0MHz
	P-Ch	—	40	60		
t <sub>d(off)</sub>	N-Ch	—	38	57	ns	P-Channel V <sub>GS</sub> = 0V, V <sub>DS</sub> = -15V, f = 1.0MHz
	P-Ch	—	42	63		
t <sub>f</sub>	N-Ch	—	31	47	ns	N-Channel V <sub>GS</sub> = 0V, V <sub>DS</sub> = -15V, f = 1.0MHz
	P-Ch	—	49	73		
C <sub>iss</sub>	N-Ch	—	900	—	pF	P-Channel V <sub>GS</sub> = 0V, V <sub>DS</sub> = -15V, f = 1.0MHz
P-Ch	—	780	—			
C <sub>oss</sub>	N-Ch	—	430	—	pF	P-Channel V <sub>GS</sub> = 0V, V <sub>DS</sub> = -15V, f = 1.0MHz
	P-Ch	—	470	—		
C <sub>rss</sub>	N-Ch	—	200	—	pF	P-Channel V <sub>GS</sub> = 0V, V <sub>DS</sub> = -15V, f = 1.0MHz
	P-Ch	—	240	—		

## Source-Drain Ratings and Characteristics


Parameter	Min.	Typ.	Max.	Units	Conditions	
						Parameter
I <sub>S</sub>	N-Ch	—	—	2.5	A	
	P-Ch	—	—	-2.5		
I <sub>SM</sub>	N-Ch	—	—	26	A	
	P-Ch	—	—	-21		
V <sub>SD</sub>	N-Ch	—	0.72	1.0	V	T <sub>J</sub> = 25°C, I <sub>S</sub> = 1.7A, V <sub>GS</sub> = 0V ③
	P-Ch	—	-0.78	-1.0		T <sub>J</sub> = 25°C, I <sub>S</sub> = -2.9A, V <sub>GS</sub> = 0V ③
t <sub>rr</sub>	N-Ch	—	52	77	ns	N-Channel T <sub>J</sub> = 25°C, I <sub>F</sub> = 1.7A, di/dt = 100A/μs ④
	P-Ch	—	47	71		
Q <sub>rr</sub>	N-Ch	—	58	86	nC	P-Channel T <sub>J</sub> = 25°C, I <sub>F</sub> = -2.9A, di/dt = 100A/μs ④
	P-Ch	—	49	73		

### Notes:


- ① Repetitive rating; pulse width limited by max. junction temperature. ( See fig. 22 )
- ② N-Channel I<sub>SD</sub> ≤ 4.1A, di/dt ≤ 92A/μs, V<sub>DD</sub> ≤ V<sub>(BR)DSS</sub>, T<sub>J</sub> ≤ 150°C  
P-Channel I<sub>SD</sub> ≤ -2.9A, di/dt ≤ -77A/μs, V<sub>DD</sub> ≤ V<sub>(BR)DSS</sub>, T<sub>J</sub> ≤ 150°C
- ③ N-Channel Starting T<sub>J</sub> = 25°C, L = 12mH R<sub>G</sub> = 25Ω, I<sub>AS</sub> = 4.1A. (See Figure 12)  
P-Channel Starting T<sub>J</sub> = 25°C, L = 35mH R<sub>G</sub> = 25Ω, I<sub>AS</sub> = -2.9A.
- ④ Pulse width ≤ 300μs; duty cycle ≤ 2%.
- ⑤ Surface mounted on FR-4 board, t ≤ 10sec.




**Fig 1.** Typical Output Characteristics



**Fig 2.** Typical Output Characteristics



**Fig 3.** Typical Transfer Characteristics




**Fig 4.** Typical Source-Drain Diode Forward Voltage


# IRF7317PbF

N-Channel


International  
**IR** Rectifier




**Fig 5.** Normalized On-Resistance Vs. Temperature




**Fig 6.** Typical On-Resistance Vs. Drain Current




**Fig 7.** Typical On-Resistance Vs. Gate Voltage




**Fig 8.** Maximum Avalanche Energy Vs. Drain Current



**Fig 9.** Typical Capacitance Vs. Drain-to-Source Voltage



**Fig 10.** Typical Gate Charge Vs. Gate-to-Source Voltage




**Fig 11.** Maximum Effective Transient Thermal Impedance, Junction-to-Ambient


# IRF7317PbF

P-Channel


International  
**IR** Rectifier




**Fig 12.** Typical Output Characteristics




**Fig 13.** Typical Output Characteristics




**Fig 14.** Typical Transfer Characteristics




**Fig 15.** Typical Source-Drain Diode Forward Voltage




**Fig 16.** Normalized On-Resistance Vs. Temperature



**Fig 17.** Typical On-Resistance Vs. Drain Current



**Fig 18.** Typical On-Resistance Vs. Gate Voltage




**Fig 19.** Maximum Avalanche Energy Vs. Drain Current


# IRF7317PbF

P-Channel


International  
**IR** Rectifier



**Fig 20.** Typical Capacitance Vs. Drain-to-Source Voltage



**Fig 21.** Typical Gate Charge Vs. Gate-to-Source Voltage




**Fig 22.** Maximum Effective Transient Thermal Impedance, Junction-to-Ambient




## SO-8 Package Outline

Dimensions are shown in millimeters (inches)




- NOTES:
1. DIMENSIONING & TOLERANCING PER ASME Y14.5M-1994.
  2. CONTROLLING DIMENSION: MILLIMETER
  3. DIMENSIONS ARE SHOWN IN MILLIMETERS (INCHES).
  4. OUTLINE CONFORMS TO JEDEC OUTLINE MS-012AA.
  5. DIMENSION DOES NOT INCLUDE MOLD PROTRUSIONS. MOLD PROTRUSIONS NOT TO EXCEED 0.15 (.006).
  6. DIMENSION DOES NOT INCLUDE MOLD PROTRUSIONS. MOLD PROTRUSIONS NOT TO EXCEED 0.25 (.010).
  7. DIMENSION IS THE LENGTH OF LEAD FOR SOLDERING TO A SUBSTRATE.



## SO-8 Part Marking Information (Lead-Free)

EXAMPLE: THIS IS AN IRF7101 (MOSFET)




# IRF7317PbF

International  
**IR** Rectifier


## SO-8 Tape and Reel

Dimensions are shown in millimeters (inches)



NOTES:

1. CONTROLLING DIMENSION : MILLIMETER.
2. ALL DIMENSIONS ARE SHOWN IN MILLIMETERS(INCHES).
3. OUTLINE CONFORMS TO EIA-481 & EIA-541.



NOTES :

1. CONTROLLING DIMENSION : MILLIMETER.
2. OUTLINE CONFORMS TO EIA-481 & EIA-541.

Data and specifications subject to change without notice.  
This product has been designed and qualified for the Consumer market.  
Qualification Standards can be found on IR's Web site.

International  
**IR** Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105

TAC Fax: (310) 252-7903

Visit us at [www.irf.com](http://www.irf.com) for sales contact information.05/04