

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

LOC DIST

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	NC	NEW RELEASE PER E.O. PI5223	2/17/97	-	RDR
	A	REVISED PER E.O. PI5827	12/31/98	-	RDR
	A1	REVISED PER ECO-13-013099	08/14/13	AM	DM

DATE CODE: YEAR IS REPRESENTED BY LAST NUMERICAL DIGIT. EX: 0=2010
MONTH IS REPRESENTED BY SEQUENTIAL ALPHA CHARACTERS. EX: A=JANUARY

CONTACT SIZE	MIN. INSUL. O.D.	MAX. INSUL. O.D.	WIRE RANGE
16	.088 [2.23]	.145 [3.68]	14-18 AWG [2.0-0.75mm ²]

3. MATERIAL - HOUSING: PLASTIC; COLOR: BLACK
SEALS: RUBBER

2. FOR CONTACT AND WIRE PERFORMANCE AND APPLICATION CHARACTERISTICS SEE ENVELOPE DRAWINGS 0425-015-0000 AND 0425-017-0000.

1. THIS PLUG MATES WITH DT04-6P-**** RECEPTACLE AND USES W6S-P012 WEDGE LOCK. (**** = ALL MODIFICATIONS) CONSULT FACTORY FOR MODIFICATIONS.

NOTES:

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN A. MALAGON 18JUL2013														
DIMENSIONS: INCHES [mm]		CHK R. MESSENGER 14AUG2013														
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD D. MEYER 14AUG2013	NAME 6 WAY PLUG COLOR: BLACK DT SERIES													
<table border="0"> <tr> <td>0 PLC</td> <td>±-</td> </tr> <tr> <td>1 PLC</td> <td>±-</td> </tr> <tr> <td>2 PLC</td> <td>±-</td> </tr> <tr> <td>3 PLC</td> <td>±.010 [0.25]</td> </tr> <tr> <td>4 PLC</td> <td>±-</td> </tr> <tr> <td>ANGLES</td> <td>±0°30'0"</td> </tr> </table>		0 PLC	±-	1 PLC	±-	2 PLC	±-	3 PLC	±.010 [0.25]	4 PLC	±-	ANGLES	±0°30'0"	PRODUCT SPEC -	SIZE A3	
0 PLC	±-															
1 PLC	±-															
2 PLC	±-															
3 PLC	±.010 [0.25]															
4 PLC	±-															
ANGLES	±0°30'0"															
MATERIAL		APPLICATION SPEC -	CAGE CODE 4AFU8	DRAWING NO DT06-6S-P012												
FINISH -		WEIGHT 9.45g	RESTRICTED TO -													
		CUSTOMER DRAWING	SCALE 5:2	SHEET 1 OF 1 REV A1												

1470-19 (3/11)