



SPECIFICATIONS								
WIRING	INPUT		OUTPUT			SHAFT ROTATION FOR VOLTAGE INCREASE	TERMINAL CONNECTIONS FOR INCREASING VOLTAGE AS VIEWED FROM TOP	
	VOLTS	HERTZ	VOLTS	CONSTANT CURRENT LOAD			INPUT	OUTPUT
THREE PHASE WYE	240	60	0-280	MAX. AMPS	MAX. KVA	CW	2-2-2	3-3-3
				50	24.2			

UNLESS OTHERWISE SPECIFIED, TOLERANCE IS #				UNITS		TITLE:		
DECIMALS	Holes	ANGLES	DRAFT	IN	MM	SPECIFICATION CONTROL DRAWING		
.XX	.125	1°	1-1/2°			VARIABLE TRANSFORMER		
.XXX	.005					5011E-3Y		
MATERIAL:				ALL DIMENSIONS APPLY AFTER PLATING		DRAWN BY		
						F. SEALE		
						DATE		
						3/7/96		
						FIRST USED ON		
						5011E-3Y		
						DO NOT SCALE DWG.		
						CUSTOMER APPROVAL		
						DATE		
						CHECKER		
						DATE		
						WEIGHT APPROX.		
						CODE IDENT. NO.		
						83008		
						DWG. SIZE		
						D		
						DWG. NO.		
						031-6742		
						SCALE		
						.25=1		
						SHEET 1 OF 1		



The information and design disclosed herein was originated by and is the property of STACO ENERGY PRODUCTS CO., which reserves all patent, proprietary, design, manufacturing, reproduction, use and sale rights thereto, and to any article disclosed therein except to the extent rights are expressly granted to others. The foregoing does not apply to vendor proprietary parts.