	T G		
4	M Thread	ØF F F F F F F F F F F F F F	
ω			LAYOUT SHOWN AS EXAMPLE
	CHARACTERISTICS	Keying Shown as example Connector dimension	
	-Standard : Based on MIL-DTL-38999 Series III-Shell Material: Aluminium-Shell Plating: Olive drab Cadmium-Insulator: Thermoplastic-Contacts: Copper Alloy	DimNominalF22.25 MaxZ31.5 MaxVV THREADM18x1-6g	SOURIAU shall not be liable for any non-conformity or damage
N	-Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minimum		CountryJurisdiction & Control ListFRNot Listed2
	-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories		PN: 8D113W35SA
	-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours		A 27-09-2016 First Release
			ISS DATE Latest modification - by MOD N° Designed By: Date: CUSTOMER DRAWING
			TITLE Aluminium Inline plug 8D series
-	BASIC SERIES:8D1-13WSHELL TYPE : In line Receptacle </td <td>35 S A ORIE</td> <td>SCALE General linear NPRDS / PROJECT NA Tolerances: ± NA ± 859 This document is the property of SOURIAU SOURIAU T(500 Matings) WWW.SOURIAU.COM</td>	35 S A ORIE	SCALE General linear NPRDS / PROJECT NA Tolerances: ± NA ± 859 This document is the property of SOURIAU SOURIAU T(500 Matings) WWW.SOURIAU.COM
	PLATING : W = Olive drab Cadmium	CONTACT LA	AYOUT : 13-35 FORMAT SOURIAU DRG N° SHEET A3 8D113W35SA-C 1/2
L	H G I	FE	$\begin{array}{ c c c c c c c c c c c c c c c c c c c$

ſ	Т	۵	н т	т		0	σ	Þ	
4	-х -	Contact Layout							4
	2 +.126 (3.20) 3 +.182 (4.62)	Contacts (Insert arrangement 13-35) Contacts (Insert arrangement 13-35) Contact Y-axis Location Y-axis (mm) Location Y-axis Position (mm) Location +.197 (5.00) 12 182 (4.62) +.088 (2.24) +.158 (4.01) +.088 (2.24) 14 045 (1.14) +.197 (5.00) +.008 (0.00) 15 +.045 (1.14) +.197 (5.00) 088 (2.24) 14 045 (1.14) +.197 (5.00) 088 (2.24) 16 +.117 (2.97) +.026 (0.66) 026 (0.26) 075 (1.91) 188 (4.01) 17 +.093 (2.36) 075 (1.91) 158 (4.01) 17 +.093 (2.36) 075 (1.91)							
ω	7 +.045 (1.14) 8 045 (1.14) 9 126 (3.20) 10 182 (4.62) 11 203 (5.16) (µ Shell size no. vol no.	197 (5.00) 18 +.000 (.00) 120 (3.05) 197 (5.00) 19 093 (2.36) 075 (1.91) 158 (4.01) 20 117 (2.97) +.026 (0.66) 088 (2.24) 21 045 (1.14) +.107 (2.72) +.000 (.00) 22 +.000 (.00) 030 (0.76)							3
						due to a use of the Pro the Specifications issued by	le for any non-conformity o ducts which does not compl either of the Parties or by a nmendation, technical notic	y with third party	
N						PN: 8D		on & Control List ot Listed	2
					A 27-09-2016 ISS DATE Designed By: TITLE	First Release Latest modification - by Date: Alun	c ninium Inline plug 8	USTOMER DRAWING	D N°
-					SCALE NA SOURIAU		ances: 	NPRDS / PROJECT 859 This document is the property of SOURIAU it must not be reproduced or communicated without permissio	
	Н	G	F	E	FORMAT A3 D		RIAU DRG N° 13W35SA-C B		IEET /2